



Catalog Number	Finish	Lamp	Wattage	Color Temp	Voltage
DML01W	White	LED	1W	3000K	120-240V
DML01SA	Satin Aluminum	LED	1W	3000K	120-240V

Feature

- Heat Sink/Driver Housing:** Die cast aluminum.
- Lens:** Injection molded acrylic sandblasted, developed for optimum optical output.
- Face Plate:** Die cast aluminum.
- Switch Box Mounting Plate:** 18ga. C.R.S. zinc plated, for mounting to a 3 1/2" deep switch box.

Electrical

LED: (1) 1W 3000K white LED. Average expected life, under normal operating conditions is 50,000 hours with lumen maintenance of 70% of original light output.

Driver: Class 2 power supply.

Voltage: 120V

Output Wattage: 1 W

Input Current (max.): 65 mA

Frequency: 50/60 Hz

Output Voltage (VDC): 4 V

Constant Current: 350 mA

Finish

Satin aluminum with protective clearcoat.
Matte white powder coat.

Labels

cULus Listed. Suitable for Dry Locations.
Wall mount only.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • B1208